

Techsolo TMV-330S

Riproduttore multimediale portatile da 3,5" – S-Ata

- Storage case per Hdd S-Ata da 3,5" con scocca in materiale plastico di qualità superiore.
- Connessione al PC o MAC tramite la porta USB 2.0 High Speed (Plug and Play).
- Connettore Video A/V : NTSC/PAL Composito (RCA).
- Connettore Video Multi-Video: S-Video, Component-YPbPr/YCbCr, VGA.
- Connettore Audio: Stereo analogico (RCA).
- Connettore ottico e coassiale per gestione formati audio digitale multicanale.



Contenuto della confezione

- TMV-330 (HDD S-Ata non incluso).
- Telecomando a raggi infrarossi. (batteria al Litio inclusa 3Volt CR2025).
- Cavo A/V (Composito e Audio RCA).
- Cavo S-Video.
- Cavo USB 2.0 ad alta velocità.
- CD con driver USB per Windows 98/SE.
- 4 viti per fissare l'HDD.
- Cacciavite a stella.
- Manuale d'uso.
- Alimentatore esterno.



Audio and video supported format			
Video	File extension	Video codec	Audio codec
	DAT	MPEG-1	MPEG-1
	VOB	MPEG-2	MPEG-2
	MPG, MPEG, M-JPG	MPEG-1, MPEG-2	MPEG-1, MPEG-2
	AVI	DivX 5, XviD	Mp3, Ac3
	AVI, MPEG-4 SP, MPEG-4 ASP, ASF		Mp3, Ac3
GMC (Global Motion Compression) and Qpel (Quarter pixel) features are not supported			
Audio	File extension	Output Bit Rate	Sampling Rate
	Mp1, Mp2, Mp3	64 ~ 192 Kbps	32 - 44,1 - 48 KHz
	Wav, Ac3	64 ~ 192 Kbps	32 - 44,1 - 48 KHz
Images	File extension	Max resolution	
	Jpg, Jpeg, Bmp	5120 x 3840	
Slideshow	Jpg and Jpeg supported		

Technical data	
Colors	Gray
Power supply	External: 110 ~ 240 V - 1 A @ 50 - 60 Hz → 12V 1,5 A / 5 V 2 A
External interface	USB-IF for USB 2.0 High Speed
Supported HDD	1 x 3,5" SATA - SATA II HDD
Transfer rate	USB2: 480Mbits/s (60 MB/s)
Chipset	ESS DMP2 ES6425FF
SATA Interface	48 bit for High capacity HDD
Packing dimension	Width: xxx mm - Length: xxx mm - Height: xxx mm
Box packing (unit)	10
Pallet (Box)	160
EAN	4039282889993